PRODUCT CATALOGUE 2025

Board Handling Equipment

Loaders, unloaders, conveyors, buffers, stackers, line routing and gate conveyors for SMT production lines.



INTRODUCTION

Built for middle and high volume production



INTEON conveyors are built for middle and high volume production, combining an attractive price with high quality performance. INTEON conveyor systems ensure optimum process stability through innovative technology. The complete electrical system meets the European quality standard and other international safety standards.

Warranty

3 years

Best in the industry warranty: 3 years full warranty.

Support - Europe

For more complex appliances our company offers the necessary training for set-up and use. We repair all products traded by our company during and after the warranty period, and we guarantee the continuous supply of accessories.

On-site visit

If any of our products has aroused your interest, INTEON will be glad to visit your company and give a presentation of the product. Major machines can also be viewed at our partners' sites.

Offers

Most of our product prices can be requested on our website and will be sent to you by email. For special and more complex machines, prices are given individually after consultation, in a price offer. For more information or user manuals, visit our continuously updated website (www.inte-on.com). You are also welcome to visit our office, where you can purchase the devices and spare parts you need.

CONTENTS

Board handling equipment

Single Magazine Loader	IE-ST-250A-ML, IE-ST-330A-ML, IE-ST-390A-ML, IE-ST-460A-ML	**6**
Single Magazine Unloader	IE-ST-250A-MU, IE-ST-330A-MU, IE-ST-390A-MU, IE-ST-460A-MU	**7**
Multi Magazine Loader	IE-CT-250A-ML, IE-CT-330A-ML, IE-CT-390A-ML, IE-CT-460A-ML	**8**
Multi Magazine Unloader	IE-CT-250A-MU, IE-CT-330A-MU, IE-CT-390A-MU, IE-CT-460A-MU	**9**
PCB Conveyor	IE-M-50LD-C, IE-L-50LD-C, IE-M-100LD-C, IE-L-100LD-C, IE-L-100LJ-C	**10**
AOI Rework Conveyor	IE-M-3/150LR-C, IE-L-3/150LR-C	**11**
PCB NG/OK Unloader	IE-CT-250A-UNG, IE-CT-330A-UNG, IE-CT-390A-UNG, IE-CT-460A-UNG	**12**
Multifunction PCB Buffer	IE-CT-350A-BL, IE-CT-400A-BL, IE-CT-460A-BL	**13**
PCB Destacker	IE-CT-350A-DU, IE-CT-400A-DU, IE-CT-460A-DU	**14**
PCB Push-up Stacker	IE-CT-350A-SU, IE-CT-400A-SU, IE-CT-460A-SU	**15**
Vacuum Bare Board Loader	IE-CT-350A-SL, IE-CT-400A-SL, IE-CT-460A-SL	**16**
PCB Turn Conveyor	IE-CT-350A-TC, IE-CT-400A-TC, IE-CT-460A-TC	**17**
PCB Inverter	IE-CT-350A-IC, IE-CT-400A-IC, IE-CT-460A-IC	**18**
Telescopic Gate Conveyor	IE-CT-350A-TG, IE-CT-400A-TG, IE-CT-460A-TG	**19**
Manual Lift Gate Conveyor	IE-CB-350A-GC, IE-CB-460A-GC	**20**
Lowering Gate Conveyor	IE-G-350L	**21**
PCB Traverser	IE-CT-350L-SC, IE-CT-460A-SC	**22**
Adjustable Multi Magazine Loader	IE-CT-460AC-ML	**23**
Adjustable Multi Magazine Unloader	IE-CT-460AC-MU	**24**
Wave Solder Outfeed Conveyor	IE-120LW	**25**

INTEON

INTEON BOARD HANDLING

3 YEARS WARRANTY

Best in the industry warranty: 3 years full warranty.



FOLLOW ME SYSTEM

Automatic width adjustment across the whole line



The width is adjusted via step motor; the FOLLOW ME system consists of an Omron PLC with Ethernet interface, touch screen and step motor.

When you set the width value on the touch screen of any of our machines in the line, the width of the other machines in the same line follows the set value automatically.

Industry 4.0 option available

Lead free

Energy saving

Eco

Flexible



LOADING & UNLOADING

Single Magazine Loader

IE-ST-250A-ML · IE-ST-330A-ML · IE-ST-390A-ML · IE-ST-460A-ML

The Single Magazine Loader is used at the start of the line for loading PCBs to the production line. The unit loads the production line automatically by pushing PCBs out of a magazine onto the conveyor of the downstream machine.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Multiple pitches selectable
- Direction from left to right, or right to left (to be defined)
- 1 magazine loading capability, discharge magazine from the rear of the machine
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-ST-250A-ML	IE-ST-330A-ML	IE-ST-390A-ML	IE-ST-460A-ML
Size	M	L	LL	XL
Power	AC 110/220 V ±10 V, 50/60 Hz			
Air Pressure	5 kgf/cm²			
PCB Size	350×(50–250) mm	460×(50–330) mm	535×(50–390) mm	535×(50–460) mm
Transfer Height	900 ± 20 mm or specify			
PCB Direction	left to right or right to left			
Magazine Rack Size	350×320×563 mm	460×400×563 mm	535×460×570 mm	535×530×570 mm
Pitches	10, 20, 30, 40 mm or specify			
Machine Dimension	1145×1030×1200 mm	1355×1120×1200 mm	1505×1310×1200 mm	1505×1450×1200 mm
Control Panel	Touch Screen (T)			

LOADING & UNLOADING

Single Magazine Unloader

IE-ST-250A-MU · IE-ST-330A-MU · IE-ST-390A-MU · IE-ST-460A-MU

The Single Magazine Unloader is used at the end of the line for unloading PCBs from the production line. An arriving PCB is taken up by the attached conveyor and then pushed into the magazine by the pusher. The magazine indexes to the next position and is ready for the following unloading cycle.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Multiple pitches selectable
- Direction from left to right, or right to left (to be defined)
- 1 magazine loading capability, discharge magazine from the rear of the machine
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-ST-250A-MU	IE-ST-330A-MU	IE-ST-390A-MU	IE-ST-460A-MU
Size	M	L	LL	XL
Power	AC 110/220 V ±10 V, 50/60 Hz			
Air Pressure	5 kgf/cm²			
PCB Size	350×(50–250) mm	460×(50–330) mm	535×(50–390) mm	535×(50–460) mm
Transfer Height	900 ± 20 mm or specify			
PCB Direction	left to right or right to left			
Magazine Rack Size	350×320×563 mm	460×400×563 mm	535×460×570 mm	535×530×570 mm
Pitches	10, 20, 30, 40 mm or specify			
Machine Dimension	1120×1030×1200 mm	1305×1120×1200 mm	1480×1310×1200 mm	1480×1450×1200 mm
Control Panel	Touch Screen (T)			

LOADING & UNLOADING

Multi Magazine Loader

IE-CT-250A-ML · IE-CT-330A-ML · IE-CT-390A-ML · IE-CT-460A-ML

The Multi Magazine Loader is used at the start of the line for loading PCBs to the production line. The unit loads the production line automatically by pushing PCBs out of a magazine onto the conveyor of the downstream machine.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Multiple pitches selectable
- Direction from left to right, or right to left (to be defined)
- 3 magazines loading capability
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-250A-ML	IE-CT-330A-ML	IE-CT-390A-ML	IE-CT-460A-ML
Size	M	L	LL	XL
Power	AC 110/220 V ±10 V, 50/60 Hz			
Air Pressure	5 kgf/cm²			
PCB Size	350×(50–250) mm	460×(50–330) mm	535×(50–390) mm	535×(50–460) mm
Transfer Height	900 ± 20 mm or specify			
PCB Direction	left to right or right to left			
Magazine Rack Size	350×320×563 mm	460×400×563 mm	535×460×570 mm	535×530×570 mm
Pitches	10, 20, 30, 40 mm or specify			
Machine Dimension	1685×745×1200 mm	1920×820×1200 mm	2165×880×1200 mm	2165×950×1200 mm
Control Panel	Touch Screen (T)			

LOADING & UNLOADING

Multi Magazine Unloader

IE-CT-250A-MU · IE-CT-330A-MU · IE-CT-390A-MU · IE-CT-460A-MU

The Multi Magazine Unloader is used at the end of the line for unloading PCBs from the production line. An arriving PCB is taken up by the attached conveyor and then pushed into the magazine by the pusher. The magazine indexes to the next position and is ready for the following unloading cycle.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Multiple pitches selectable
- Direction from left to right, or right to left (to be defined)
- 3 magazines loading capability
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-250A-MU	IE-CT-330A-MU	IE-CT-390A-MU	IE-CT-460A-MU
Size	M	L	LL	XL
Power	AC 110/220 V ±10 V, 50/60 Hz			
Air Pressure	5 kgf/cm²			
PCB Size	350×(50–250) mm	460×(50–330) mm	535×(50–390) mm	535×(50–460) mm
Transfer Height	900 ± 20 mm or specify			
PCB Direction	left to right or right to left			
Magazine Rack Size	350×320×563 mm	460×400×563 mm	535×460×570 mm	535×530×570 mm
Pitches	10, 20, 30, 40 mm or specify			
Machine Dimension	1685×745×1200 mm	1920×820×1200 mm	2165×880×1200 mm	2165×950×1200 mm
Control Panel	Touch Screen (T)			

CONVEYORS

PCB Conveyor

IE-M-50LD-C · IE-L-50LD-C · IE-M-100LD-C · IE-L-100LD-C · IE-L-100LJ-C

The PCB Conveyor is used in the PCB assembly line when frequent visual inspection of PCBs is required. It can be used as an inspection conveyor or a linking conveyor.



Industry 4.0 option available | **FOLLOW ME System compatible**

FEATURES

- ✓ PLC control system
- ✓ Width adjusting system by hand crank. Electrical width adjustment by switch available on request
- ✓ Variable speed control
- ✓ Multi-zone concept available on request
- ✓ CE certified
- ✓ Metal fabricated frame
- ✓ Automatic width adjustment
- ✓ Inspection and bypass mode selectable
- ✓ SMEMA compliant

SPECIFICATIONS

Model	IE-M-50LD-C	IE-L-50LD-C	IE-M-100LD-C	IE-L-100LD-C	IE-L-100LJ-C
Conveyor Length	500 mm		1000 mm		1000 mm
Power	AC 110/220 V ±10 V, 50/60 Hz				
PCB Width	50–350 mm (-M), 50–460 mm (-L)				
Transfer Speed	1–12 m/min adjustable				
Transfer Height	900 ± 20 mm				
PCB Direction	left to right or right to left				
Working Light	N		N		Y
Machine Dimension	500×650×900 mm		1000×650×900 mm		1000×650×900 mm

CONVEYORS

AOI Rework Conveyor

IE-M-3/150LR-C · IE-L-3/150LR-C

The AOI Rework Conveyor is used for good/bad PCB separation. The center segment moves up/down pneumatically, allowing separation without interrupting the flow of good PCBs.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Width adjustment by hand crank. Electrical width adjustment by switch available on request
- Rework and bypass mode selectable
- 3 belt segments, providing the possibility to buffer one failed PCB
- SMEMA compliant
- CE certified
- Automatic width adjustment

SPECIFICATIONS

Model	IE-M-3/150LR-C	IE-L-3/150LR-C
Power Supply	AC 110/220 V ±10 V, 50/60 Hz	
Air Supply	5 kgf/cm²	
PCB Width	50–350 mm	50–460 mm
Transfer Height	900 ± 20 mm	
PCB Direction	left to right or right to left	
Machine Size	1500×760×1100 mm	1500×860×1100 mm

LOADING & UNLOADING

PCB NG/OK Unloader

IE-CT-250A-UNG · IE-CT-330A-UNG · IE-CT-390A-UNG · IE-CT-460A-UNG

The PCB NG/OK Unloader is used for good/bad PCB separation. After being tested by a test machine, OK and NG PCBs can be separated and sent to magazines.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Easy touch screen operation
- Good and bad PCBs can be separated automatically with magazine rack
- Multiple pitches selectable
- Direction from left to right, or right to left (to be defined)
- 3 magazines for good PCBs, 3 magazines for bad PCBs loading capability
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-250A-UNG	IE-CT-330A-UNG	IE-CT-390A-UNG	IE-CT-460A-UNG
Size	M	L	LL	XL
Power	AC 110/220 V ±10 V, 50/60 Hz			
Air Pressure	5 kgf/cm²			
PCB Size	350×(50–250) mm	460×(50–330) mm	535×(50–390) mm	535×(50–460) mm
Transfer Height	900 ± 20 mm or specify			
PCB Direction	left to right or right to left			
Magazine Rack Size	350×320×563 mm	460×400×563 mm	535×460×570 mm	535×530×570 mm
Pitches	multiple			
Machine Dimension	1510×1460×1200 mm	1910×1630×1200 mm	2160×1760×1200 mm	2160×1900×1200 mm

BUFFERING & STACKING

Multifunction PCB Buffer

IE-CT-350A-BL · IE-CT-400A-BL · IE-CT-460A-BL

The Multifunction PCB Buffer is used to buffer PCBs in LIFO or FIFO mode. “Pass-through” mode may be selected so that the PCB is transferred through it, or “Automatic” mode may be selected so that the machine is used as a PCB buffer.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Servo motor, Omron PLC control system, touch screen operation
- 3 operative modes: FIFO (first in first out), LIFO (last in first out), pass through
- Storage capability of 24 PCBs
- Electrical width adjustment
- Direction from left to right or right to left (optional)
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-350A-BL	IE-CT-400A-BL	IE-CT-460A-BL
Power Supply		AC 110/220 V ±10 V, 50/60 Hz	
Air Supply		5 kgf/cm²	
PCB Size	400×(50–350) mm	460×(50–400) mm	535×(50–460) mm
Buffer capacity		Max. 24 PCBs at pitch 1	
Transfer Height		900 ± 20 mm	
PCB Direction		left to right or right to left	
Machine Size	500×885×1650 mm	610×935×1650 mm	610×995×1650 mm

BUFFERING & STACKING

PCB Destacker

IE-CT-350A-DU · IE-CT-400A-DU · IE-CT-460A-DU

The PCB Destacker is used for loading bare boards onto the PCB assembly line. A mechanism separates the bottom PCB from the stacker and lowers it onto the edge belt conveyor.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Easy touch screen operation
- Bypass mode selectable
- Automatic electrical width adjustment
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-350A-DU	IE-CT-400A-DU	IE-CT-460A-DU
Power Supply		AC 110/220 V ±10 V, 50/60 Hz	
Air Supply		5 kgf/cm²	
PCB Size	400×(50–350) mm	460×(50–400) mm	535×(50–460) mm
Buffer capacity		Max. 24 PCBs at pitch 1	
Transfer Height		900 ± 20 mm	
PCB Direction		left to right or right to left	
Machine Size	630×850×1250 mm	630×900×1250 mm	630×950×1250 mm

BUFFERING & STACKING

PCB Push-up Stacker

IE-CT-350A-SU · IE-CT-400A-SU · IE-CT-460A-SU

The Push-up Stacker is used for restacking unpopulated boards at the end of the line. Stacking is done by a pneumatic lifter, which gently raises the PCBs from the belt conveyor and adds them, one by one, to the bottom of the stack.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Easy touch screen operation
- Bypass mode selectable
- Automatic electrical width adjustment
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-350A-SU	IE-CT-400A-SU	IE-CT-460A-SU
Power Supply		AC 110/220 V ±10 V, 50/60 Hz	
Air Supply		5 kgf/cm²	
PCB Size	400×(50–350) mm	460×(50–400) mm	535×(50–460) mm
Transfer Height		900 ± 20 mm	
PCB Direction		left to right or right to left	
Machine Size	630×850×1250 mm	630×900×1250 mm	630×950×1250 mm

BUFFERING & STACKING

Vacuum Bare Board Loader

IE-CT-350A-SL · IE-CT-400A-SL · IE-CT-460A-SL

The Bare Board Loader is used for automatically loading unpopulated boards at the beginning or in the middle of a PCB assembly line. The bare boards are lifted one by one from the stack by vacuum and gently lowered onto the belt segment, ready for the downstream machine.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Bypass mode selectable
- Flexible suction design, position adjustable
- Sucking stability improved by using a single vacuum generator system
- Width adjusting system by hand crank. Electrical width adjustment available on request
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-350A-SL	IE-CT-400A-SL	IE-CT-460A-SL
Power Supply		AC 110/220 V ±10 V, 50/60 Hz	
Air Supply		5 kgf/cm²	
PCB Size	400×(50–350) mm	460×(50–400) mm	535×(50–460) mm
Transfer Height		900 ± 20 mm	
PCB Direction		left to right or right to left	
Machine Size	700×735×1250 mm	750×785×1250 mm	800×835×1250 mm
Control Panel		Touch Screen (T)	

LINE ROUTING

PCB Turn Conveyor

IE-CT-350A-TC · IE-CT-400A-TC · IE-CT-460A-TC

The 90° PCB Turn Conveyor is used for changing the direction of flow of a PCB assembly line. The PCB is transferred onto the built-in belt conveyor, which turns either 90° clockwise or counter clockwise.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Bypass mode selectable
- Width adjusting system by hand crank. Electrical width adjustment available on request
- Sensor protection for safer operation
- Motor-controlled rotation, smooth and accurate
- SMEMA compliant
- CE certified
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-350A-TC	IE-CT-400A-TC	IE-CT-460A-TC
Power Supply	AC 110/220 V ±10 V, 50/60 Hz		
Air Supply	5 kgf/cm²		
PCB Size	400×(50–350) mm	460×(50–400) mm	535×(50–460) mm
Transfer Height	900 ± 20 mm		
PCB Direction	90° clockwise or counter clockwise (option)		
Machine Size	700×700×1200 mm	750×750×1200 mm	800×800×1200 mm
Control Panel	Touch Screen (T)		

LINE ROUTING

PCB Inverter

IE-CT-350A-IC · IE-CT-400A-IC · IE-CT-460A-IC

The PCB Inverter is used for inverting PCBs, so that the board can be processed on both sides without manual handling.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Bypass mode selectable
- Width adjusting system by hand crank. Electrical width adjustment available on request
- Sensor protection for safer operation
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-350A-IC	IE-CT-400A-IC	IE-CT-460A-IC
Power Supply		AC 110/220 V ±10 V, 50/60 Hz	
Air Supply		5 kgf/cm²	
PCB Size	400×(50–350) mm	460×(50–400) mm	535×(50–460) mm
Transfer Height		900 ± 20 mm	
PCB Direction		left to right or right to left	
Machine Size	500×800×1250 mm	550×850×1250 mm	600×900×1300 mm
Control Panel		Touch Screen (T)	

GATE CONVEYORS

Telescopic Gate Conveyor

IE-CT-350A-TG · IE-CT-400A-TG · IE-CT-460A-TG

The Telescopic Gate Conveyor is used for creating a passage in the PCB assembly line to give the operator access to the rear of the production equipment. The integrated conveyor segment slides across the opening upon request from the downstream machine when a board enters the unit. The conveyor returns to its retracted home position as the board is released, leaving a normally open passage in the line.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Fully opening gate passage allows free operator access
- Electrical width adjustment
- Through beam sensors for additional safety
- Electrically driven for smooth extension and retraction
- SMEMA compliant
- CE certified
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-350A-TG	IE-CT-400A-TG	IE-CT-460A-TG
Power Supply		AC 110/220 V ±10 V, 50/60 Hz	
Air Supply		5 kgf/cm²	
PCB Size	400×(50–350) mm	460×(50–400) mm	535×(50–460) mm
Walkway		Max. 900 mm adjustable	
Transfer Height		900 ± 20 mm	
PCB Direction		left to right or right to left	
Machine Size	(750–1700)×740×1100 mm	(750–1700)×790×1100 mm	(750–1700)×840×1100 mm
Control Panel		Touch Screen (T)	

GATE CONVEYORS

Manual Lift Gate Conveyor

IE-CB-350A-GC · IE-CB-460A-GC

The Manual Lift Gate Conveyor is used when a passageway is required in a production line. By manually lifting the conveyor section, access is gained to the rear of the line (semiautomatic).



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Cylinder assisted lifting motion
- Width adjustment by hand crank
- Pneumatic locking device installed to enhance safety
- SMEMA compliant
- CE certified
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CB-350A-GC	IE-CB-460A-GC
Power Supply	AC 110/220 V ±10 V, 50/60 Hz	
Air Supply	5 kgf/cm²	
PCB Size	400×(50–350) mm	460×(50–400) mm
Walkway	600 mm	
Transfer Height	900 ± 20 mm	
PCB Direction	left to right or right to left	
Machine Size	1000×650×1100 mm	1000×750×1100 mm

GATE CONVEYORS

Lowering Gate Conveyor

IE-G-350L

The Lowering Gate Conveyor is used when a passageway is required in a production line (semiautomatic).



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- PLC control system
- Lowering and lifting of the gate conveyor by cylinder
- Width adjustment by hand crank
- Sensor protection for safer operation
- SMEMA compliant
- Automatic width adjustment

SPECIFICATIONS

Model	IE-G-350L
Power Supply	AC 110/220 V ±10 V, 50/60 Hz
Air Supply	5 kgf/cm²
PCB Size	50×50–400×350 mm
Transport Height	900 ± 20 mm
PCB Direction	left to right or right to left
Machine Size	1300×560×1250 mm

LINE ROUTING

PCB Traverser

IE-CT-350L-SC · IE-CT-460A-SC

The PCB Traverser is used for transporting boards from one line into two lines or vice versa. The orientation of the board is not changed during traversing.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Servo motor, Omron PLC control system, touch screen operation
- Width adjustment by hand crank. Electrical width adjustment by switch available on request
- Bypass mode selectable
- Traversing length to specification
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-350L-SC	IE-CT-460A-SC
Power Supply	AC 110/220 V ±10 V, 50/60 Hz	
Air Supply	5 kgf/cm²	
PCB Width	50–350 mm	50–460 mm
Traversing Length	specified	
Transfer Height	900 ± 20 mm	
PCB Direction	left to right or right to left	
Machine Size	according to traversing length	

LOADING & UNLOADING

Adjustable Multi Magazine Loader

IE-CT-460AC-ML

The Adjustable Multi Magazine Loader is used at the start of the line for loading PCBs to the production line. The unit loads the production line automatically by pushing PCBs out of a magazine onto the conveyor of the downstream machine.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Multiple pitches selectable
- Direction from left to right, or right to left (to be defined)
- 3 magazines loading capability
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-460AC-ML
Power	AC 110/220 V ±10 V, 50/60 Hz
Air Pressure	5 kgf/cm²
PCB Size	min. 50×50 mm, max. 535×460 mm
Transfer Height	900 ± 20 mm or specify
PCB Direction	left to right or right to left
Magazine Rack Size	355×320×563 mm, 460×400×563 mm, 535×460×570 mm, 535×530×570 mm
Pitches	10, 20, 30, 40 mm or specify
Machine Dimension	1750×1100×1190 mm
Control Panel	Touch Screen (T)

LOADING & UNLOADING

Adjustable Multi Magazine Unloader

IE-CT-460AC-MU

The Adjustable Multi Magazine Unloader is used at the end of the line for unloading PCBs from the production line. An arriving PCB is taken up by the attached conveyor and then pushed into the magazine by the pusher. The magazine indexes to the next position and is ready for the following unloading cycle.



Industry 4.0 option available

FOLLOW ME System compatible

FEATURES

- Omron PLC control system
- Touch screen control is standard
- Multiple pitches selectable
- Direction from left to right, or right to left (to be defined)
- 3 magazines loading capability
- SMEMA compliant
- CE certified
- Safety cover is standard for CE conveyors
- Automatic width adjustment

SPECIFICATIONS

Model	IE-CT-460AC-MU
Power	AC 110/220 V ±10 V, 50/60 Hz
Air Pressure	5 kgf/cm²
PCB Size	min. 50×50 mm, max. 535×460 mm
Transfer Height	900 ± 20 mm or specify
PCB Direction	left to right or right to left
Magazine Rack Size	355×320×563 mm, 460×400×563 mm, 535×460×570 mm, 535×530×570 mm
Pitches	10, 20, 30, 40 mm or specify
Machine Dimension	2500×1100×1150 mm
Control Panel	Touch Screen (T)

CONVEYORS

Wave Solder Outfeed Conveyor

IE-120LW

The Wave Solder Outfeed Conveyor is used to unload PCBs from the inclined conveyors of wave solder and then lower the soldered boards to a standard conveyor height.



FOLLOW ME System compatible

FEATURES

- Angle adjustment at input and output ends
- Heat-resistant ESD belt with non-slip surface
- Heavy-duty aluminum construction
- Optional fan attachment for extra cooling capacity
- CE certified
- Automatic width adjustment

SPECIFICATIONS

Model	IE-120LW
Power Supply	AC 110/220 V ±10 V, 50/60 Hz
PCB Width	50–450 mm
PCB Direction	left to right or right to left
Machine Size	1200×500×(750–1200) mm

INTEON PRODUCT RANGE

More from INTEON



REFLOW OVENS



CONVEYORS



BGA REWORKS



DRY CABINETS



ESD RACKS

Full product range

www.inte-on.com

INTEON

ALSO FROM INTEON

Reflow ovens

- Economic
- Lead free
- Energy saving
- Flexible



INTEON

www.inte-on.com

MANUFACTURER

INTEON Corporation Limited

RM A07, 1701-02 New Trend Centre
704 Prince Edward Road East
San Po Kong, KLN, Hong Kong
E-mail: **info@inte-on.com**

DISTRIBUTOR FOR EUROPE

InterElectronic Hungary Kft.

2461 Tárnok, Pacsirtamező 3 D/1
Károly Peics **+36 30 296 45 05**
David Peics **+36 30 217 1226**
E-mail: **info@interelectronic.com**

VE-1/2025